

dow.com/submittalsEMEA dow.com/contactus

# DECLARATION OF PERFORMANCE No SNF\_DOP\_031

1. Unique identification code of the product-type:

# **Dowsil™ 785N Neutral Sanitary Silicone Clear**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

## **Batch number: see product packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

## Sealants for sanitary joints: EN-15651-3: S (Class XS2)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Dow Europe GmbH
Bachtobelstrasse 3
8810 Horgen
Switzerland

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

#### **Not relevant**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

## System 3; System 3 for reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Notify body SKZ - Testing GmbH (NB 1213)
Friedrich-Bergius-Ring 22
97076 Würzburg
Germany

performed the initial type testing according to EN 15651-3 and reaction to fire under system 3 and issued a: test report.

**Disclaimer:** The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, The Dow Chemical Company makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.



8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

#### **Not relevant**

### 9. Declared performance

Essential Characteristics	Declared performance	Technical Standard
Reaction to fire	Class E	UNE-EN-ISO 11925-2:2011
Release of chemicals	None	See product safety data sheet
Water tightness & air tightness as determined by:		
Resistance to flow – according ISO 7390	≤ 3 mm	EN 15651- 3
Loss of volume – according ISO 10563	≤ 25%	EN 15651-3
Adhesion/cohesion at maintained extension after immersion in water – EN ISO 10590	No Failure	EN 15651- 3
Microbiological growth – according EN ISO 846:1997	1	EN 15651-3
Durability	Pass	EN 15651- 3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

# **Not relevant**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Sebastien Dath High Performance Building AETS Manager EMEA

Sebastien.dath@dow.com

Seneffe, 28 January 2022