

## Product Information Sheet

### Vi-Pro® EASY TO TOOL

Version: 2

Revision date: 03.07.2023

### **Vi-Pro® Easy To Tool Liquid for Sealant Tooling (concentrated)**

#### **Description:**

Vi-Pro Easy To Tool Liquid for Sealant Tooling is a concentrated smoothing agent, aqueous solution made of surfactants and additives, used to smooth silicone, polyurethane, polysulfide and hybrid sealants. The product is water based, and is safe for the workers. Vi-Pro Easy to Tool is suitable for tooling secondary sealants in insulating glass and also as a separating agent for use on racks.

#### **Advantages:**

- Keeps the shine of the sealant surface intact.
- Colouring pigments of the sealant are not washed off.
- Dermatologically tested ingredients.
- Does not dry out the skin.
- Suitable for all sealants.
- Prevents IG units from sticking to the racks.
- Free of acids, lye and solvents; neutral.

#### **Characteristics:**

Colour:	colourless
Density:	1.02 - 1.04
Temperature for application:	5°C - 30°C
Shelf life:	12 months
Chemical nature:	aqueous solution of surfactants

#### **Instructions for use in tooling joints:**

1. Dilute Vi-Pro Easy To Tool with clean water in ratio 1:20 to 1:5 (5% - 20%).
2. Moisten your finger resp. the smoothing tools with the diluted Vi-Pro Easy To Tool or spray the diluted product with an atomizer on the sealing joint and smooth the joint.
3. Remove surplus of Vi-Pro Easy To Tool with clean water, since it may cause stains on some surfaces (e.g. natural stone).
4. Vi-Pro Easy To Tool should not remain in larger amounts on the sealing joint and dry out. The dried out residues may lead to optic disturbances of the sealant's surface (mat/light stains).
5. Before use test the compatibility with adjacent surfaces, such as coated wood or fresh painted surfaces.

## Product Information Sheet

### Vi-Pro® EASY TO TOOL

**Version: 2**

**Revision date: 03.07.2023**

6. Do not pour diluted Vi-Pro Easy To Tool back into the original container.
7. Always use fresh Vi-Pro Easy To Tool.
8. Due to the many possible influences during and after application, the customer always has to carry out trials first.

#### **Instructions for use as separating agent for use on racks:**

1. Apply concentrated liquid with sponge, roller or spray.
2. Immerse the base of the rack (ca. 30 min)
3. In the case of highly absorbent wood, repeat the operation several times
4. The racks can be used immediately after drying.

#### **Storage:**

Store in unopened, original containers between 5°C and 25°C for maximum 12 months. Please observe the recommended shelf life which is printed on the packaging. Opened containers should be used within one month.

#### **Packaging:**

Vi-Pro Easy To Tool is available in containers of 1 litre. 9 cans per box.

#### **Safety precautions**

Material Safety Data Sheets are available on demand. MSDS are provided to help customers satisfy their own handling, safety and disposal needs and those that may be required by locally applicable health and safety regulations. MSDS are updated regularly, therefore, please request and review the most current MSDS before handling or using any product.

Never burn away.

In use, may form highly flammable vapour-air mixture. Keep away from sources of ignition.

Do not breathe vapour and spray.

Use only in well-ventilated areas. Keep out of reach of children.

#### **Customer notice**

The information supplied is accurate to the best of our knowledge and is based on reliable tests and practical experiences. Properties quoted are intended, as a guide and do not therefore constitute a specification. Customer/user should thoroughly test any application to be sure that product corresponds to the required performances. The Seller shall not be liable for any incidental or consequential damages.

More information available at: +48 22 122 85 49 or [reach@vi-pro.eu](mailto:reach@vi-pro.eu)