Technical Data Sheet

Vi-Pro® MANUAL GUN 2K (1:1 MS), 400ML

Wersja: 1-EN

Date: 17.10.2024

Vi-Pro® MANUAL GUN 2K (1:1 MS), 400ML



Professional applicator with aluminium body. Die-cast steel lever.

PVC-coated handle and rod release button. Rod release button and die-cast aluminium retract rod knob.

For the use of medium/high viscosity glues and sealants, in two-component side by side cartidges.

Characteristics:

WAY OF EXTRUSION	MECHANICAL (rod driven piston)
Art. Code	VIPRO-G400M
Net weight	988 g
Clutch	Tempered – two piece
Push Rod	High carbon steel
Max force	450 Kgf – 4,4 kN
Thrust ratio	24:1
Progress / Stroke	3,5 mm
PVC Soft-touch	3 point black

Packaging

Single packing.

Note to customer:

The information provided is true to the best of our knowledge and is based on reliable tests and practical experience. The specified properties are indicative and therefore do

Technical Data Sheet

Vi-Pro® MANUAL GUN 2K (1:1 MS), 400ML

Wersja: 1-EN

Date: 17.10.2024

not constitute specifications. The customer/user should thoroughly test each application to ensure that the product meets the required parameters. The only warranty is that the product conforms to the sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to a refund of the purchase price or replacement of any product found to be other than the warranted product. Seller is not liable for incidental or consequential damages.

More information available at: +48 22 122 85 49 or reach@vi-pro.eu