

Technical Data Sheet

Vi-Pro® PNEUMATIC GUN FOR 993

Wersja: 1-EN

Date: 17.10.2024

Vi-Pro® PNEUMATIC GUN FOR 993



Professional pneumatic applicator for the extrusion of all type high viscosity and chemical anchor products, packed in side by side cartridges 490 ml ratio 10:1.

Characteristics:

WAY OF EXTRUSION	MECHANICAL (rod driven piston)
Art. Code	VIPRO-G9
Net weight	3.650 kg
Work pressure	0-10 bar
Total length	520 mm
Max force	380 Kgf (10 bar – 145 PSI) – 3,72 kN
Connection	¼ male gas
Noise level	<80dBA
Features	Pressure reducer integrated Dump value integrated (dripless) Pneumatic return

Packaging

Single packing.

Technical Data Sheet

Vi-Pro® PNEUMATIC GUN FOR 993

Wersja: 1-EN

Date: 17.10.2024

Note to customer:

The information provided is true to the best of our knowledge and is based on reliable tests and practical experience. The specified properties are indicative and therefore do not constitute specifications. The customer/user should thoroughly test each application to ensure that the product meets the required parameters. The only warranty is that the product conforms to the sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to a refund of the purchase price or replacement of any product found to be other than the warranted product. Seller is not liable for incidental or consequential damages.

More information available at: +48 22 122 85 49 or reach@vi-pro.eu