

## Technical Data Sheet

### Vi-Pro® Window Tape Vario

Wersja: 1-EN

Date: 12.03.2025

### Vi-Pro® Window Tape Vario

#### Product description:

Vi-Pro® Window Tape Vario is a tape that secures the filling of the gap between the joinery and the walls in certain circumstances. The tape can be used both inside and outside the partition.

#### Advantages:

- The back of the tape is fully covered by a high-quality adhesive, which guarantees a tight connection to the most popular construction materials.
- The adhesive is protected by silicone-coated film with finger lift, which facilitates peeling off the liner.
- The product in PLATINUM+ version is equipped with an additional self-adhesive strip on the top side, which is meant for application to the window or door frame.
- The structure of the surface tape facilitates plastering and optimizes the adhesion of cement based adhesives.
- The product is odorless and does not contain VOC and hazardous substances.

#### Technical Data:

PROPERTY	TEST METHOD	RESULT
Length [m]	PN-EN 1848-2:2003	5 do 80 (-0,0/+0,2)
Width [mm]	PN-EN 1848-2:2003	5 do 400 (±2,0)
Maximum tensile strength [MPa]	PN-EN 12311-2:2002 method B	
- longitudinal direction		>200
- transverse direction		>90
Elongation at maximum force [%]	PN-EN 12311-2:2002 method B	
- longitudinal direction		>20
- transverse direction		>150
Water vapour permeability sd [m]	PN-EN ISO 12572:2004 method A and method C	1,5 < sd < 18,5
Peel strength (steel plate) [N/10mm]	PN-EN ISO 29862:2019	≥ 12,5
Watertightness	PN-EN 1928:2002 2 godz. / 200 mm H2O	No leaks
Temperature of application		from -10°C to +35°C
Working temperature		from -40°C to +80°C

## Technical Data Sheet

### Vi-Pro® Window Tape Vario

Wersja: 1-EN

Date: 12.03.2025

---

**Application:**

The tape is intended for sealing the gap between a window or door and a wall on the outside and on the inside.

**Storage:**

Store in dry place at +1°C to +25°C, in an original packaging for 24 months.

**Application instruction:**

The surface to which the tape is going to be applied should be dry, degreased and free of dirt. The product can be used at -10°C only when conditioned at around 15 °C to 20 °C at least 2 hours. Unwind the product from the roll and apply it to one side of the joint. Cut to the required length, peel off the protective film, then press it to the other side of the joint. **Window joinery processing should be completed up to 3 months after installing the tape or protected against direct sunlight.**

**Waste handling:**

The raw materials and the product itself are not classified as dangerous substances. The remains of the tapes and the disassembly material is plastic waste. Treat the protective film as mixed packaging waste and cardboard boxes along with cardboard dividers as packaging waste made of paper and cardboard.

**Cleaning:**

Products can be removed mechanically. Residuals can be cleaned with an organic solvent, such as acetone - provided that the solvent does not damage the surface.

**Safety instructions:**

General health and safety guidelines apply:

- it is forbidden to eat, drink and smoke during work,
- try to avoid contact with skin and eyes,
- wash hands before breaks or at the end of work.

If you need more information, please contact our Customer Service.

**Precautions:**

Material safety data sheets are available upon request. Product Safety Data Sheets are provided to help customers meet their own handling, safety and disposal needs and those that may be required by local health and safety regulations. Safety data sheets are

## Technical Data Sheet

### Vi-Pro® Window Tape Vario

Wersja: 1-EN

Date: 12.03.2025

---

updated regularly, so please request and read the latest version of the safety data sheet before handling or using any product.

**Note to customer:**

The information provided is true to the best of our knowledge and is based on reliable tests and practical experience. The specified properties are indicative and therefore do not constitute specifications. The customer/user should thoroughly test each application to ensure that the product meets the required parameters. The only warranty is that the product conforms to the sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to a refund of the purchase price or replacement of any product found to be other than the warranted product. Seller is not liable for incidental or consequential damages.

More information available at: +48 22 122 85 49 or [reach@vi-pro.eu](mailto:reach@vi-pro.eu)